



Part Number	CF 6207 A0
Series	CF 62
Drain Grooves	No

Material¹

Inner Ring	Aluminum
Outer Ring	Aluminum

Shaft & Housing Tolerances

Shaft Tolerance	k5
Housing Tolerance	J6
Shaft & Housing Surface	Rz ≤ 16µm ; Ra ≤ 3.2µm

Dimensions

Bore Diameter	ID [mm]	35
Outer Diameter	OD [mm]	72
Width	W [mm]	6
Minor Gap Diameter	e ₁ [mm]	48
Major Gap Diameter	e ₂ [mm]	58
Axial Clearance ²	S _{ax} [mm]	1

Misc. Data

Weight	[kg]	0.050
Max Speed ³	[rpm]	28,090
Temperature Range	[°C]	-40 – 200

Notes:

1. Other materials available on request.
 2. Axial Clearance (S_{ax}) = The total axial movement of the seal's inner ring in relation to the outer ring in the axial direction.
 3. The stated speed value is contingent on utilizing specified tolerances, correct installation techniques, and an operating temperature below the specified maximum. CF60/619 Seals are installed between the spindle bearing and the shaft nut. This prevents any axial mobility and removes the need for a speed limit.
 4. Installation example with preload transferred through seal.
 5. Installation example with gap between seal and bearing.
 6. Mounting aid suggested to ensure proper axial alignment after installation.
- * Contact GMN USA engineers for any technical assistance.

