



Part Number	RA 463 Z
Type	Complete Freewheel Clutch Unit
Spring	Z (Tension)
Sealed	Yes
Lubrication	Oil
Inner Ring Keyway	Yes
Outer Ring Keyway	Mounting Tab
Integrated Ball Bearing	Yes
Integrated Roller	Yes

Geometrical Data

Bore Diameter	d [mm]	35
Outer Diameter	D [mm]	100
Mounting Tab Length	F [mm]	92
Mounting Tab Hole Spacing	E [mm]	68
Mounting Tab Width	W [mm]	50
Mounting Tab Thickness	A [mm]	16
Mounting Tab Bore	C [mm]	16
Keyway Width	b [mm]	10
Keyway Depth	t [mm]	3.3
Weight	[kg]	1.75

Shaft & Housing Tolerances

Shaft Tolerance	k5
Housing Tolerance	N/A
Shaft & Housing	1mm x 15°

Ratings

Nominal Torque	[Nm]	428
Nominal Torque	[ft-lb]	315.7
Max. Static Radial Load	[N]	17,063
Max. Dynamic Radial Load	[N]	13,070
Max. Indexing Frequency	[Hz]	10
Max. Speed ²	[rpm]	1,100
Max. Operating Temperature	[°C]	110

Notes:

1. The stated speed and torque ratings are contingent on utilizing specified tolerances, correct installation techniques, and operating temperature and load conditions below the specified maximums. If specific applications differ, please consult GMN USA engineers.
2. The stated RPM value is for the maximum freewheel rotational speed for the sprags, not the shaft or housing. High freewheel rotational speeds can produce centrifugal forces that can cause the sprags to lift off from frictional contact, therefore creating an opportunity for improper engagement and potential slip. The sprag RPM must be below the listed value before engagement occurs. The actual sprag freewheel speed is difficult to determine because the sprags are driven by frictional forces from the race(s) and lubrication. Theoretically there is no maximum rotational speed in the driving direction; the inner race, sprags, and outer race rotate as one unit unaffected by centrifugal forces. Please consult GMN USA engineers with high RPM applications that approach or exceed the stated RPM rating.