



Part Number	HY SM 61915 C TA
Bearing Size	61915

Bearing Series	SM
Hybrid (Si ₃ N ₄ Balls)	Yes

Bearing Dimensions

Bore Diameter	d [mm]	75
Outer Diameter	D [mm]	105
Bearing Width	B [mm]	16
Pitch Circle	d _m [mm]	90.0
Ball Diameter	D _w [mm]	8.731
OD Inner Ring	d ₁ [mm]	84.7
ID Outer Ring	D ₁ [mm]	95.3
ID Outer Ring (Open Side)	D ₂ [mm]	98.8
Chamfer	r _{1,2} [mm]	0.6
Chamfer (Open Side)	r _{3,4} [mm]	0.3

Geometrical Data

Number of Balls	Z [Qty.]	25
Contact Angle	α ₀ [°]	19
Bearing Weight	m [kg]	0.350

Mating Part Dimensions

Abutment Diameter Inner Ring	d _a min. [mm]	81.0
Abutment Diameter Outer Ring	D _a max. [mm]	99.5
Chamfer Associated Component	r _a max. [mm]	0.6
Chamfer Associated Component (Open Side)	r _b max. [mm]	0.3

Bearing Load Ratings

Dynamic Radial Load Rating	C [N]	20,800
Static Radial Load Rating Steel Balls	C ₀ [N]	16,000
Static Radial Load Rating Si ₃ N ₄ balls	C _{0 HY} [N]	11,300

Bearing Preload Data

Light Pre-Load	F _v [N]	110
Light Axial Rigidity	C _{ax} [N/μm]	78
Medium Pre-Load	F _v [N]	320
Medium Axial Rigidity	C _{ax} [N/μm]	116
Heavy Pre-Load	F _v [N]	640
Heavy Axial Rigidity	C _{ax} [N/μm]	153
Minimum Spring Pre-Load	F _r [N]	800

Bearing RPM Ratings

Speed Value with Oil Lubrication	n _{oil} [1/min]	27,500
Speed Value with Grease Lubrication	n _{grease} [1/min]	20,625

Notes:

1. Position of the oiling Nozzle (d_r) for bearings with TA cage/ TXM cage upon request
2. The stated load and speed values are given for a spring preloaded single bearing with oil/air or oil mist lubrication. If specific applications differ, please consult correction factors and/or GMN USA engineers.