



Part Number	S 61803 E TA
Bearing Size	61803

Bearing Series	S
Hybrid (Si ₃ N ₄ Balls)	No

Bearing Dimensions

Bore Diameter	d [mm]	17
Outer Diameter	D [mm]	26
Bearing Width	B [mm]	5
Pitch Circle	d _m [mm]	21.5
Ball Diameter	D _w [mm]	2.381
OD Inner Ring	d ₁ [mm]	19.8
ID Outer Ring	D ₁ [mm]	23.2
ID Outer Ring (Open Side)	D ₂ [mm]	23.8
Chamfer	r _{1,2} [mm]	0.3
Chamfer (Open Side)	r _{3,4} [mm]	0.2

Geometrical Data

Number of Balls	Z [Qty.]	19
Contact Angle	α ₀ [°]	25
Bearing Weight	m [kg]	0.008

Mating Part Dimensions

Abutment Diameter Inner Ring	d _a min. [mm]	19.0
Abutment Diameter Outer Ring	D _a max. [mm]	24.0
Chamfer Associated Component	r _a max. [mm]	0.3
Chamfer Associated Component (Open Side)	r _b max. [mm]	0.15

Bearing Load Ratings

Dynamic Radial Load Rating	C [N]	1,890
Static Radial Load Rating Steel Balls	C ₀ [N]	1,240
Static Radial Load Rating Si ₃ N ₄ balls	C _{0HY} [N]	870

Bearing Preload Data

Light Pre-Load	F _v [N]	16
Light Axial Rigidity	C _{ax} [N/μm]	35
Medium Pre-Load	F _v [N]	50
Medium Axial Rigidity	C _{ax} [N/μm]	54
Heavy Pre-Load	F _v [N]	100
Heavy Axial Rigidity	C _{ax} [N/μm]	69
Minimum Spring Pre-Load	F _l [N]	70

Bearing RPM Ratings

Speed Value with Oil Lubrication	n _{oil} [1/min]	67,000
Speed Value with Grease Lubrication	n _{grease} [1/min]	50,000

Notes:

1. Position of the oiling Nozzle (dT) for bearings with TA cage/ TXM cage upon request
2. The stated load and speed values are given for a spring preloaded single bearing with oil/air or oil mist lubrication. If specific applications differ, please consult correction factors and/or GMN USA engineers.