



Part Number	S 61914 E TA
Bearing Size	61914

Bearing Series	S
Hybrid (Si ₃ N ₄ Balls)	No

Bearing Dimensions

Bore Diameter	d [mm]	70
Outer Diameter	D [mm]	100
Bearing Width	B [mm]	16
Pitch Circle	d _m [mm]	85.0
Ball Diameter	D _w [mm]	7.938
OD Inner Ring	d ₁ [mm]	80.1
ID Outer Ring	D ₁ [mm]	89.9
ID Outer Ring (Open Side)	D ₂ [mm]	92.7
Chamfer	r _{1,2} [mm]	1.0
Chamfer (Open Side)	r _{3,4} [mm]	0.3

Geometrical Data

Number of Balls	Z [Qty.]	24
Contact Angle	α ₀ [°]	25
Bearing Weight	m [kg]	0.346

Mating Part Dimensions

Abutment Diameter Inner Ring	d _a min. [mm]	76.0
Abutment Diameter Outer Ring	D _a max. [mm]	94.5
Chamfer Associated Component	r _a max. [mm]	0.6
Chamfer Associated Component (Open Side)	r _b max. [mm]	0.3

Bearing Load Ratings

Dynamic Radial Load Rating	C [N]	23,000
Static Radial Load Rating Steel Balls	C ₀ [N]	24,500
Static Radial Load Rating Si ₃ N ₄ balls	C _{0HY} [N]	17,300

Bearing Preload Data

Light Pre-Load	F _v [N]	200
Light Axial Rigidity	C _{ax} [N/μm]	165
Medium Pre-Load	F _v [N]	590
Medium Axial Rigidity	C _{ax} [N/μm]	247
Heavy Pre-Load	F _v [N]	1,180
Heavy Axial Rigidity	C _{ax} [N/μm]	329
Minimum Spring Pre-Load	F _r [N]	840

Bearing RPM Ratings

Speed Value with Oil Lubrication	n _{oil} [1/min]	17,000
Speed Value with Grease Lubrication	n _{grease} [1/min]	12,500

Notes:

1. Position of the oiling Nozzle (d_r) for bearings with TA cage/ TXM cage upon request
2. The stated load and speed values are given for a spring preloaded single bearing with oil/air or oil mist lubrication. If specific applications differ, please consult correction factors and/or GMN USA engineers.