



Part Number	SM 6013 C TA
Bearing Size	6013

Bearing Series	SM
Hybrid (Si ₃ N ₄ Balls)	No

Bearing Dimensions

Bore Diameter	d [mm]	65
Outer Diameter	D [mm]	100
Bearing Width	B [mm]	18
Pitch Circle	d _m [mm]	82.5
Ball Diameter	D _w [mm]	9.525
OD Inner Ring	d ₁ [mm]	76.9
ID Outer Ring	D ₁ [mm]	88.2
ID Outer Ring (Open Side)	D ₂ [mm]	92.0
Chamfer	r _{1,2} [mm]	1.1
Chamfer (Open Side)	r _{3,4} [mm]	1.0

Geometrical Data

Number of Balls	Z [Qty.]	23
Contact Angle	α ₀ [°]	15
Bearing Weight	m [kg]	0.431

Mating Part Dimensions

Abutment Diameter Inner Ring	d _a min. [mm]	72.0
Abutment Diameter Outer Ring	D _a max. [mm]	93.0
Chamfer Associated Component	r _a max. [mm]	1.1
Chamfer Associated Component (Open Side)	r _b max. [mm]	0.6

Bearing Load Ratings

Dynamic Radial Load Rating	C [N]	25,000
Static Radial Load Rating Steel Balls	C ₀ [N]	18,400
Static Radial Load Rating Si ₃ N ₄ balls	C _{0 HY} [N]	13,000

Bearing RPM Ratings

Speed Value with Oil Lubrication	n _{oil} [1/min]	24,000
Speed Value with Grease Lubrication	n _{grease} [1/min]	18,000

Bearing Preload Data

Light Pre-Load	F _v [N]	130
Light Axial Rigidity	C _{ax} [N/μm]	58
Medium Pre-Load	F _v [N]	380
Medium Axial Rigidity	C _{ax} [N/μm]	91
Heavy Pre-Load	F _v [N]	760
Heavy Axial Rigidity	C _{ax} [N/μm]	123
Minimum Spring Pre-Load	F _r [N]	760

Notes:

1. Position of the oiling Nozzle (d_r) for bearings with TA cage/ TXM cage upon request
2. The stated load and speed values are given for a spring preloaded single bearing with oil/air or oil mist lubrication. If specific applications differ, please consult correction factors and/or GMN USA engineers.