



KSK DEEP GROOVE BALL BEARINGS

SERIES 600

**DEEP GROOVE BALL BEARINGS
 SERIES 600**

KSK Bearing Number	Bore d		Out.Dia. D		Width B		Approx. Net Weight (kg)	(Interchange)						FAG SKF(Eur) STEYR
	mm	inches	mm	inches	mm	inches		ADR	FAF	MRC	ND	RMB	SKF	
635	5.000	0.1969	19.000	0.7480	6.000	0.2362	0.008	635	35K	35	35	R5190	635	635
626	6.000	0.2362	19.000	0.7480	6.000	0.2362	0.008	626	36K	36	36	R6190	626	626
626-1/4	6.350	0.2500	19.000	0.7480	6.000	0.2362	0.008							
636	6.000	0.2362	22.000	0.8661	7.000	0.2756	0.014							
607	7.000	0.2756	19.000	0.7480	6.000	0.2362	0.008	607				R7190	607	607
627	7.000	0.2756	22.000	0.8661	7.000	0.2756	0.013	627	37K	37	37	R7220	627	627
637	7.000	0.2756	26.000	1.0236	9.000	0.3543	0.024							
608	8.000	0.3150	22.000	0.8661	7.000	0.2756	0.012	608	38K	38	38	R8220	608	608
608-5/16	7.937	0.3125	22.000	0.8661	7.000	0.2756	0.012							
628	8.000	0.3150	24.000	0.9449	8.000	0.3150	0.015							
638	8.000	0.3150	28.000	1.1024	9.000	0.3543	0.028							
609	9.000	0.3543	24.000	0.9449	7.000	0.2756	0.014	609					609	609
629	9.000	0.3543	26.000	1.0236	8.000	0.3150	0.020	629	39K	39	39		629	629
639	9.000	0.3543	30.000	1.1811	10.000	0.3937	0.035							

- Note:
- (1) Also available double shielded (ZZ) and double sealed (2RS). No change in width dimensions.
 - (2) C3 and C4 radial clearances are available on all of the above sizes.
 - (3) Also available in ABEC 3 and 5 precision. Consult for availability.