



Part Number	CF 6210 A0
Series	CF 62
Drain Grooves	No

Material¹

Inner Ring	Aluminum
Outer Ring	Aluminum

Shaft & Housing Tolerances

Shaft Tolerance	k5
Housing Tolerance	J6
Shaft & Housing Surface	Rz ≤ 16µm ; Ra ≤ 3.2µm

Dimensions

Bore Diameter	ID [mm]	50
Outer Diameter	OD [mm]	90
Width	W [mm]	6
Minor Gap Diameter	e ₁ [mm]	63
Major Gap Diameter	e ₂ [mm]	73
Axial Clearance ²	S _{ax} [mm]	1

Misc. Data

Weight	[kg]	0.071
Max Speed ³	[rpm]	19,810
Temperature Range	[°C]	-40 – 200

Notes:

- Other materials available on request.
 - Axial Clearance (S_{ax}) = The total axial movement of the seal's inner ring in relation to the outer ring in the axial direction.
 - The stated speed value is contingent on utilizing specified tolerances, correct installation techniques, and an operating temperature below the specified maximum. CF60/619 Seals are installed between the spindle bearing and the shaft nut. This prevents any axial mobility and removes the need for a speed limit.
 - Installation example with preload transferred through seal.
 - Installation example with gap between seal and bearing.
 - Mounting aid suggested to ensure proper axial alignment after installation.
- * Contact GMN USA engineers for any technical assistance.

