



Part Number	KH 61905 E TA
Bearing Size	61905

Bearing Series	KH
Hybrid (Si ₃ N ₄ Balls)	No

Bearing Dimensions

Bore Diameter	d [mm]	25
Outer Diameter	D [mm]	42
Bearing Width	B [mm]	9
Pitch Circle	d _m [mm]	33.5
Ball Diameter	D _w [mm]	3.969
OD Inner Ring	d ₁ [mm]	30.6
OD Inner Ring (Open Side)	d ₂ [mm]	30.0
ID Outer Ring	D ₁ [mm]	37.2
ID Outer Ring (Open Side)	D ₂ [mm]	38.5
Chamfer	r _{1,2} [mm]	0.3
Chamfer (Open Side)	r _{3,4} [mm]	0.3

Geometrical Data

Number of Balls	Z [Qty.]	19
Contact Angle	α ₀ [°]	25
Bearing Weight	m [kg]	0.041

Mating Part Dimensions

Abutment Diameter Inner Ring	d _{a,b} min. [mm]	28.0
Abutment Diameter Outer Ring	D _{a,b} max. [mm]	38.5
Chamfer Associated Component	r _a max. [mm]	0.3
Chamfer Associated Component (Open Side)	r _b max. [mm]	0.15

Bearing Load Ratings

Dynamic Radial Load Rating	C [N]	4,100
Static Radial Load Rating Steel Balls	C ₀ [N]	2,220
Static Radial Load Rating Si ₃ N ₄ balls	C _{0 HY} [N]	1,560

Bearing Preload Data

Light Pre-Load	F _v [N]	35
Light Axial Rigidity	C _{ax} [N/μm]	52
Medium Pre-Load	F _v [N]	100
Medium Axial Rigidity	C _{ax} [N/μm]	76
Heavy Pre-Load	F _v [N]	200
Heavy Axial Rigidity	C _{ax} [N/μm]	99
Minimum Spring Pre-Load	F _f [N]	195

Bearing RPM Ratings

Speed Value with Oil Lubrication	n _{oil} [1/min]	57,000
Speed Value with Grease Lubrication	n _{grease} [1/min]	43,000

Notes:

1. Position of the oiling Nozzle (d_T) for bearings with TA cage/ TXM cage upon request
2. The stated load and speed values are given for a spring preloaded single bearing with oil/air or oil mist lubrication. If specific applications differ, please consult correction factors and/or GMN USA engineers.