



Part Number	<b>KH 61906 E TA</b>
Bearing Size	61906

Bearing Series	KH
Hybrid (Si <sub>3</sub> N <sub>4</sub> Balls)	No

### Bearing Dimensions

Bore Diameter	d [mm]	30
Outer Diameter	D [mm]	47
Bearing Width	B [mm]	9
Pitch Circle	d <sub>m</sub> [mm]	38.5
Ball Diameter	D <sub>w</sub> [mm]	3.969
OD Inner Ring	d <sub>1</sub> [mm]	35.1
OD Inner Ring (Open Side)	d <sub>2</sub> [mm]	35.0
ID Outer Ring	D <sub>1</sub> [mm]	41.7
ID Outer Ring (Open Side)	D <sub>2</sub> [mm]	43.0
Chamfer	r <sub>1,2</sub> [mm]	0.3
Chamfer (Open Side)	r <sub>3,4</sub> [mm]	0.3

### Geometrical Data

Number of Balls	Z [Qty.]	22
Contact Angle	α <sub>0</sub> [°]	25
Bearing Weight	m [kg]	0.047

### Mating Part Dimensions

Abutment Diameter Inner Ring	d <sub>a,b</sub> min. [mm]	33.0
Abutment Diameter Outer Ring	D <sub>a,b</sub> max. [mm]	43.5
Chamfer Associated Component	r <sub>a</sub> max. [mm]	0.3
Chamfer Associated Component (Open Side)	r <sub>b</sub> max. [mm]	0.15

### Bearing Load Ratings

Dynamic Radial Load Rating	C [N]	4,400
Static Radial Load Rating Steel Balls	C <sub>0</sub> [N]	2,650
Static Radial Load Rating Si <sub>3</sub> N <sub>4</sub> balls	C <sub>0 HY</sub> [N]	1,840

### Bearing Preload Data

Light Pre-Load	F <sub>v</sub> [N]	35
Light Axial Rigidity	C <sub>ax</sub> [N/μm]	58
Medium Pre-Load	F <sub>v</sub> [N]	110
Medium Axial Rigidity	C <sub>ax</sub> [N/μm]	87
Heavy Pre-Load	F <sub>v</sub> [N]	220
Heavy Axial Rigidity	C <sub>ax</sub> [N/μm]	112
Minimum Spring Pre-Load	F <sub>f</sub> [N]	210

### Bearing RPM Ratings

Speed Value with Oil Lubrication	n <sub>oil</sub> [1/min]	50,000
Speed Value with Grease Lubrication	n <sub>grease</sub> [1/min]	37,000

### Notes:

1. Position of the oiling Nozzle (d<sub>T</sub>) for bearings with TA cage/ TXM cage upon request
2. The stated load and speed values are given for a spring preloaded single bearing with oil/air or oil mist lubrication. If specific applications differ, please consult correction factors and/or GMN USA engineers.