



| | |
|---|-------------|
| Part Number | 6201 |
| Bearing Series | Radial |
| Hybrid (Si ₃ N ₄ Balls) | No |

Geometrical Data

| | | |
|-----------------|----------|-------|
| Number of Balls | Z [Qty.] | 7 |
| Bearing Weight | m [kg] | 0.037 |

Bearing Load Ratings¹

| | | |
|--|----------------------|-------|
| Dynamic Radial Load Rating | C [N] | 6,650 |
| Static Radial Load Rating Steel Balls | C ₀ [N] | 2,950 |
| Static Radial Load Rating Si ₃ N ₄ balls | C _{0HY} [N] | 2,070 |

Bearing RPM Ratings²

| | | |
|-------------------------------------|-----------------------------|--------|
| Speed Value with Oil Lubrication | n _{oil} [1/min] | 63,000 |
| Speed Value with Grease Lubrication | n _{grease} [1/min] | 50,400 |

Bearing Dimensions

| | | |
|----------------|-----------------------|-------|
| Bore Diameter | d [mm] | 12 |
| Outer Diameter | D [mm] | 32 |
| Bearing Width | B [mm] | 10 |
| Pitch Circle | d _m [mm] | 22.0 |
| Ball Diameter | D _w [mm] | 5.953 |
| OD Inner Ring | d ₁ [mm] | 18.3 |
| ID Outer Ring | D ₁ [mm] | 26.0 |
| Chamfer | r _{1,2} [mm] | 0.6 |

Mating Part Dimensions

| | | |
|------------------------------|--------------------------|------|
| Abutment Diameter Inner Ring | d _a min. [mm] | 16.5 |
| Abutment Diameter Outer Ring | D _a max. [mm] | 27.5 |
| Chamfer Associated Component | r _a max. [mm] | 0.6 |

Notes:

1. The stated load ratings are given for a single bearing with grease lubrication. If specific applications differ, please consult GMN USA engineers.
2. Speed ratings are for phenolic outer land guided cage (TA). Please consult the full GMN Bearing catalog or GMN USA engineers for speed ratings of different cages.