



Part Number	HY S 61807 C TA
Bearing Size	61807

Bearing Series	S
Hybrid (Si ₃ N ₄ Balls)	Yes

Bearing Dimensions

Bore Diameter	d [mm]	35
Outer Diameter	D [mm]	47
Bearing Width	B [mm]	7
Pitch Circle	d _m [mm]	41.0
Ball Diameter	D _w [mm]	3.175
OD Inner Ring	d ₁ [mm]	38.9
ID Outer Ring	D ₁ [mm]	43.1
ID Outer Ring (Open Side)	D ₂ [mm]	44.1
Chamfer	r _{1,2} [mm]	0.3
Chamfer (Open Side)	r _{3,4} [mm]	0.3

Geometrical Data

Number of Balls	Z [Qty.]	24
Contact Angle	α ₀ [°]	15
Bearing Weight	m [kg]	0.028

Mating Part Dimensions

Abutment Diameter Inner Ring	d _a min. [mm]	38.0
Abutment Diameter Outer Ring	D _a max. [mm]	44.0
Chamfer Associated Component	r _a max. [mm]	0.3
Chamfer Associated Component (Open Side)	r _b max. [mm]	0.15

Bearing Load Ratings

Dynamic Radial Load Rating	C [N]	3,950
Static Radial Load Rating Steel Balls	C ₀ [N]	3,600
Static Radial Load Rating Si ₃ N ₄ balls	C _{0HY} [N]	2,550

Bearing Preload Data

Light Pre-Load	F _v [N]	20
Light Axial Rigidity	C _{ax} [N/μm]	25
Medium Pre-Load	F _v [N]	60
Medium Axial Rigidity	C _{ax} [N/μm]	39
Heavy Pre-Load	F _v [N]	120
Heavy Axial Rigidity	C _{ax} [N/μm]	54
Minimum Spring Pre-Load	F _r [N]	105

Bearing RPM Ratings

Speed Value with Oil Lubrication	n _{oil} [1/min]	51,250
Speed Value with Grease Lubrication	n _{grease} [1/min]	38,750

Notes:

1. Position of the oiling Nozzle (dT) for bearings with TA cage/ TXM cage upon request
2. The stated load and speed values are given for a spring preloaded single bearing with oil/air or oil mist lubrication. If specific applications differ, please consult correction factors and/or GMN USA engineers.