



Part Number	HY S 61905 C TA
Bearing Size	61905

Bearing Series	S
Hybrid (Si ₃ N ₄ Balls)	Yes

Bearing Dimensions

Bore Diameter	d [mm]	25
Outer Diameter	D [mm]	42
Bearing Width	B [mm]	9
Pitch Circle	d _m [mm]	33.5
Ball Diameter	D _w [mm]	4.762
OD Inner Ring	d ₁ [mm]	30.6
ID Outer Ring	D ₁ [mm]	37.4
ID Outer Ring (Open Side)	D ₂ [mm]	38.7
Chamfer	r _{1,2} [mm]	0.3
Chamfer (Open Side)	r _{3,4} [mm]	0.3

Geometrical Data

Number of Balls	Z [Qty.]	17
Contact Angle	α ₀ [°]	15
Bearing Weight	m [kg]	0.041

Mating Part Dimensions

Abutment Diameter Inner Ring	d _a min. [mm]	28.0
Abutment Diameter Outer Ring	D _a max. [mm]	38.5
Chamfer Associated Component	r _a max. [mm]	0.3
Chamfer Associated Component (Open Side)	r _b max. [mm]	0.15

Bearing Load Ratings

Dynamic Radial Load Rating	C [N]	7,700
Static Radial Load Rating Steel Balls	C ₀ [N]	5,400
Static Radial Load Rating Si ₃ N ₄ balls	C _{0HY} [N]	3,800

Bearing Preload Data

Light Pre-Load	F _v [N]	40
Light Axial Rigidity	C _{ax} [N/μm]	29
Medium Pre-Load	F _v [N]	120
Medium Axial Rigidity	C _{ax} [N/μm]	48
Heavy Pre-Load	F _v [N]	240
Heavy Axial Rigidity	C _{ax} [N/μm]	67
Minimum Spring Pre-Load	F _r [N]	200

Bearing RPM Ratings

Speed Value with Oil Lubrication	n _{oil} [1/min]	62,500
Speed Value with Grease Lubrication	n _{grease} [1/min]	46,250

Notes:

1. Position of the oiling Nozzle (d_r) for bearings with TA cage/ TXM cage upon request
2. The stated load and speed values are given for a spring preloaded single bearing with oil/air or oil mist lubrication. If specific applications differ, please consult correction factors and/or GMN USA engineers.