



Part Number	HY SM 6022 C TA
Bearing Size	6022

Bearing Series	SM
Hybrid (Si ₃ N ₄ Balls)	Yes

Bearing Dimensions

Bore Diameter	d [mm]	110
Outer Diameter	D [mm]	170
Bearing Width	B [mm]	28
Pitch Circle	d _m [mm]	140.0
Ball Diameter	D _w [mm]	17.462
OD Inner Ring	d ₁ [mm]	129.4
ID Outer Ring	D ₁ [mm]	150.6
ID Outer Ring (Open Side)	D ₂ [mm]	157.5
Chamfer	r _{1,2} [mm]	2.0
Chamfer (Open Side)	r _{3,4} [mm]	1.0

Geometrical Data

Number of Balls	Z [Qty.]	21
Contact Angle	α ₀ [°]	17
Bearing Weight	m [kg]	1.980

Mating Part Dimensions

Abutment Diameter Inner Ring	d _a min. [mm]	121.0
Abutment Diameter Outer Ring	D _a max. [mm]	159.0
Chamfer Associated Component	r _a max. [mm]	2.0
Chamfer Associated Component (Open Side)	r _b max. [mm]	1.0

Bearing Load Ratings

Dynamic Radial Load Rating	C [N]	70,000
Static Radial Load Rating Steel Balls	C ₀ [N]	55,000
Static Radial Load Rating Si ₃ N ₄ balls	C _{0 HY} [N]	39,000

Bearing Preload Data

Light Pre-Load	F _v [N]	360
Light Axial Rigidity	C _{ax} [N/μm]	115
Medium Pre-Load	F _v [N]	1,070
Medium Axial Rigidity	C _{ax} [N/μm]	174
Heavy Pre-Load	F _v [N]	2,140
Heavy Axial Rigidity	C _{ax} [N/μm]	232
Minimum Spring Pre-Load	F _r [N]	2,380

Bearing RPM Ratings

Speed Value with Oil Lubrication	n _{oil} [1/min]	18,125
Speed Value with Grease Lubrication	n _{grease} [1/min]	13,750

Notes:

1. Position of the oiling Nozzle (d_r) for bearings with TA cage/ TXM cage upon request
2. The stated load and speed values are given for a spring preloaded single bearing with oil/air or oil mist lubrication. If specific applications differ, please consult correction factors and/or GMN USA engineers.