



Part Number	HY SM 609 C TA
Bearing Size	609

Bearing Series	SM
Hybrid (Si ₃ N ₄ Balls)	Yes

Bearing Dimensions

Bore Diameter	d [mm]	9
Outer Diameter	D [mm]	24
Bearing Width	B [mm]	7
Pitch Circle	d _m [mm]	16.5
Ball Diameter	D _w [mm]	3.969
OD Inner Ring	d ₁ [mm]	13.5
ID Outer Ring	D ₁ [mm]	19.9
ID Outer Ring (Open Side)	D ₂ [mm]	20.6
Chamfer	r _{1,2} [mm]	0.3
Chamfer (Open Side)	r _{3,4} [mm]	0.3

Geometrical Data

Number of Balls	Z [Qty.]	10
Contact Angle	α ₀ [°]	15
Bearing Weight	m [kg]	0.014

Mating Part Dimensions

Abutment Diameter Inner Ring	d _a min. [mm]	11.5
Abutment Diameter Outer Ring	D _a max. [mm]	21.0
Chamfer Associated Component	r _a max. [mm]	0.3
Chamfer Associated Component (Open Side)	r _b max. [mm]	0.1

Bearing Load Ratings

Dynamic Radial Load Rating	C [N]	2,950
Static Radial Load Rating Steel Balls	C ₀ [N]	1,150
Static Radial Load Rating Si ₃ N ₄ balls	C _{0 HY} [N]	810

Bearing Preload Data

Light Pre-Load	F _v [N]	16
Light Axial Rigidity	C _{ax} [N/μm]	12
Medium Pre-Load	F _v [N]	50
Medium Axial Rigidity	C _{ax} [N/μm]	20
Heavy Pre-Load	F _v [N]	100
Heavy Axial Rigidity	C _{ax} [N/μm]	27
Minimum Spring Pre-Load	F _r [N]	90

Bearing RPM Ratings

Speed Value with Oil Lubrication	n _{oil} [1/min]	150,000
Speed Value with Grease Lubrication	n _{grease} [1/min]	112,500

Notes:

1. Position of the oiling Nozzle (d_T) for bearings with TA cage/ TXM cage upon request
2. The stated load and speed values are given for a spring preloaded single bearing with oil/air or oil mist lubrication. If specific applications differ, please consult correction factors and/or GMN USA engineers.