



Part Number	HY SM 61902 C TA
Bearing Size	61902

Bearing Series	SM
Hybrid (Si ₃ N ₄ Balls)	Yes

Bearing Dimensions

Bore Diameter	d [mm]	15
Outer Diameter	D [mm]	28
Bearing Width	B [mm]	7
Pitch Circle	d _m [mm]	21.5
Ball Diameter	D _w [mm]	3.969
OD Inner Ring	d ₁ [mm]	18.7
ID Outer Ring	D ₁ [mm]	24.3
ID Outer Ring (Open Side)	D ₂ [mm]	25.4
Chamfer	r _{1,2} [mm]	0.3
Chamfer (Open Side)	r _{3,4} [mm]	0.3

Geometrical Data

Number of Balls	Z [Qty.]	13
Contact Angle	α ₀ [°]	15
Bearing Weight	m [kg]	0.015

Mating Part Dimensions

Abutment Diameter Inner Ring	d _a min. [mm]	17.5
Abutment Diameter Outer Ring	D _a max. [mm]	25.5
Chamfer Associated Component	r _a max. [mm]	0.3
Chamfer Associated Component (Open Side)	r _b max. [mm]	0.1

Bearing Load Ratings

Dynamic Radial Load Rating	C [N]	3,600
Static Radial Load Rating Steel Balls	C ₀ [N]	1,560
Static Radial Load Rating Si ₃ N ₄ balls	C _{0HY} [N]	1,100

Bearing Preload Data

Light Pre-Load	F _v [N]	18
Light Axial Rigidity	C _{ax} [N/μm]	15
Medium Pre-Load	F _v [N]	55
Medium Axial Rigidity	C _{ax} [N/μm]	24
Heavy Pre-Load	F _v [N]	110
Heavy Axial Rigidity	C _{ax} [N/μm]	33
Minimum Spring Pre-Load	F _r [N]	110

Bearing RPM Ratings

Speed Value with Oil Lubrication	n _{oil} [1/min]	116,250
Speed Value with Grease Lubrication	n _{grease} [1/min]	87,500

Notes:

1. Position of the oiling Nozzle (dT) for bearings with TA cage/ TXM cage upon request
2. The stated load and speed values are given for a spring preloaded single bearing with oil/air or oil mist lubrication. If specific applications differ, please consult correction factors and/or GMN USA engineers.