



Part Number	HY SM 61912 C TA
Bearing Size	61912

Bearing Series	SM
Hybrid (Si ₃ N ₄ Balls)	Yes

Bearing Dimensions

Bore Diameter	d [mm]	60
Outer Diameter	D [mm]	85
Bearing Width	B [mm]	13
Pitch Circle	d _m [mm]	72.5
Ball Diameter	D _w [mm]	7.144
OD Inner Ring	d ₁ [mm]	68.1
ID Outer Ring	D ₁ [mm]	76.9
ID Outer Ring (Open Side)	D ₂ [mm]	79.5
Chamfer	r _{1,2} [mm]	1.0
Chamfer (Open Side)	r _{3,4} [mm]	0.3

Geometrical Data

Number of Balls	Z [Qty.]	23
Contact Angle	α ₀ [°]	19
Bearing Weight	m [kg]	0.195

Mating Part Dimensions

Abutment Diameter Inner Ring	d _a min. [mm]	65.0
Abutment Diameter Outer Ring	D _a max. [mm]	80.0
Chamfer Associated Component	r _a max. [mm]	0.6
Chamfer Associated Component (Open Side)	r _b max. [mm]	0.3

Bearing Load Ratings

Dynamic Radial Load Rating	C [N]	14,100
Static Radial Load Rating Steel Balls	C ₀ [N]	10,300
Static Radial Load Rating Si ₃ N ₄ balls	C _{0 HY} [N]	7,200

Bearing Preload Data

Light Pre-Load	F _v [N]	70
Light Axial Rigidity	C _{ax} [N/μm]	61
Medium Pre-Load	F _v [N]	220
Medium Axial Rigidity	C _{ax} [N/μm]	93
Heavy Pre-Load	F _v [N]	430
Heavy Axial Rigidity	C _{ax} [N/μm]	122
Minimum Spring Pre-Load	F _r [N]	540

Bearing RPM Ratings

Speed Value with Oil Lubrication	n _{oil} [1/min]	34,375
Speed Value with Grease Lubrication	n _{grease} [1/min]	25,625

Notes:

1. Position of the oiling Nozzle (d_r) for bearings with TA cage/ TXM cage upon request
2. The stated load and speed values are given for a spring preloaded single bearing with oil/air or oil mist lubrication. If specific applications differ, please consult correction factors and/or GMN USA engineers.