



Part Number	S 6014 E TA
Bearing Size	6014

Bearing Series	S
Hybrid (Si ₃ N ₄ Balls)	No

Bearing Dimensions

Bore Diameter	d [mm]	70
Outer Diameter	D [mm]	110
Bearing Width	B [mm]	20
Pitch Circle	d _m [mm]	90.0
Ball Diameter	D _w [mm]	11.906
OD Inner Ring	d ₁ [mm]	82.6
ID Outer Ring	D ₁ [mm]	97.4
ID Outer Ring (Open Side)	D ₂ [mm]	101.7
Chamfer	r _{1,2} [mm]	1.1
Chamfer (Open Side)	r _{3,4} [mm]	1.0

Geometrical Data

Number of Balls	Z [Qty.]	21
Contact Angle	α ₀ [°]	25
Bearing Weight	m [kg]	0.593

Mating Part Dimensions

Abutment Diameter Inner Ring	d _a min. [mm]	77.0
Abutment Diameter Outer Ring	D _a max. [mm]	102.0
Chamfer Associated Component	r _a max. [mm]	1.1
Chamfer Associated Component (Open Side)	r _b max. [mm]	0.6

Bearing Load Ratings

Dynamic Radial Load Rating	C [N]	46,000
Static Radial Load Rating Steel Balls	C ₀ [N]	43,500
Static Radial Load Rating Si ₃ N ₄ balls	C _{0HY} [N]	30,500

Bearing Preload Data

Light Pre-Load	F _v [N]	400
Light Axial Rigidity	C _{ax} [N/μm]	200
Medium Pre-Load	F _v [N]	1,200
Medium Axial Rigidity	C _{ax} [N/μm]	310
Heavy Pre-Load	F _v [N]	2,400
Heavy Axial Rigidity	C _{ax} [N/μm]	420
Minimum Spring Pre-Load	F _l [N]	1,670

Bearing RPM Ratings

Speed Value with Oil Lubrication	n _{oil} [1/min]	16,000
Speed Value with Grease Lubrication	n _{grease} [1/min]	12,000

Notes:

1. Position of the oiling Nozzle (d_T) for bearings with TA cage/ TXM cage upon request
2. The stated load and speed values are given for a spring preloaded single bearing with oil/air or oil mist lubrication. If specific applications differ, please consult correction factors and/or GMN USA engineers.