



Part Number	<b>S 6022 E TA</b>
Bearing Size	6022

Bearing Series	S
Hybrid (Si <sub>3</sub> N <sub>4</sub> Balls)	No

**Bearing Dimensions**

Bore Diameter	d [mm]	110
Outer Diameter	D [mm]	170
Bearing Width	B [mm]	28
Pitch Circle	d <sub>m</sub> [mm]	140.0
Ball Diameter	D <sub>w</sub> [mm]	17.462
OD Inner Ring	d <sub>1</sub> [mm]	129.4
ID Outer Ring	D <sub>1</sub> [mm]	150.6
ID Outer Ring (Open Side)	D <sub>2</sub> [mm]	157.5
Chamfer	r <sub>1,2</sub> [mm]	2.0
Chamfer (Open Side)	r <sub>3,4</sub> [mm]	1.0

**Geometrical Data**

Number of Balls	Z [Qty.]	21
Contact Angle	α <sub>0</sub> [°]	25
Bearing Weight	m [kg]	1.980

**Mating Part Dimensions**

Abutment Diameter Inner Ring	d <sub>a</sub> min. [mm]	121.0
Abutment Diameter Outer Ring	D <sub>a</sub> max. [mm]	159.0
Chamfer Associated Component	r <sub>a</sub> max. [mm]	2.0
Chamfer Associated Component (Open Side)	r <sub>b</sub> max. [mm]	1.0

**Bearing Load Ratings**

Dynamic Radial Load Rating	C [N]	94,000
Static Radial Load Rating Steel Balls	C <sub>0</sub> [N]	100,000
Static Radial Load Rating Si <sub>3</sub> N <sub>4</sub> balls	C <sub>0HY</sub> [N]	70,000

**Bearing Preload Data**

Light Pre-Load	F <sub>v</sub> [N]	790
Light Axial Rigidity	C <sub>ax</sub> [N/μm]	310
Medium Pre-Load	F <sub>v</sub> [N]	2,380
Medium Axial Rigidity	C <sub>ax</sub> [N/μm]	470
Heavy Pre-Load	F <sub>v</sub> [N]	4,760
Heavy Axial Rigidity	C <sub>ax</sub> [N/μm]	625
Minimum Spring Pre-Load	F <sub>r</sub> [N]	3,450

**Bearing RPM Ratings**

Speed Value with Oil Lubrication	n <sub>oil</sub> [1/min]	10,500
Speed Value with Grease Lubrication	n <sub>grease</sub> [1/min]	7,900

**Notes:**

1. Position of the oiling Nozzle (dT) for bearings with TA cage/ TXM cage upon request
2. The stated load and speed values are given for a spring preloaded single bearing with oil/air or oil mist lubrication. If specific applications differ, please consult correction factors and/or GMN USA engineers.