



Part Number	S 61806 C TA
Bearing Size	61806

Bearing Series	S
Hybrid (Si ₃ N ₄ Balls)	No

Bearing Dimensions

Bore Diameter	d [mm]	30
Outer Diameter	D [mm]	42
Bearing Width	B [mm]	7
Pitch Circle	d _m [mm]	36.0
Ball Diameter	D _w [mm]	3.175
OD Inner Ring	d ₁ [mm]	34.1
ID Outer Ring	D ₁ [mm]	38.3
ID Outer Ring (Open Side)	D ₂ [mm]	39.3
Chamfer	r _{1,2} [mm]	0.3
Chamfer (Open Side)	r _{3,4} [mm]	0.3

Geometrical Data

Number of Balls	Z [Qty.]	22
Contact Angle	α ₀ [°]	15
Bearing Weight	m [kg]	0.025

Mating Part Dimensions

Abutment Diameter Inner Ring	d _a min. [mm]	33.0
Abutment Diameter Outer Ring	D _a max. [mm]	39.0
Chamfer Associated Component	r _a max. [mm]	0.3
Chamfer Associated Component (Open Side)	r _b max. [mm]	0.15

Bearing Load Ratings

Dynamic Radial Load Rating	C [N]	3,850
Static Radial Load Rating Steel Balls	C ₀ [N]	3,250
Static Radial Load Rating Si ₃ N ₄ balls	C _{0HY} [N]	2,280

Bearing Preload Data

Light Pre-Load	F _v [N]	20
Light Axial Rigidity	C _{ax} [N/μm]	24
Medium Pre-Load	F _v [N]	60
Medium Axial Rigidity	C _{ax} [N/μm]	37
Heavy Pre-Load	F _v [N]	120
Heavy Axial Rigidity	C _{ax} [N/μm]	52
Minimum Spring Pre-Load	F _r [N]	100

Bearing RPM Ratings

Speed Value with Oil Lubrication	n _{oil} [1/min]	47,000
Speed Value with Grease Lubrication	n _{grease} [1/min]	35,000

Notes:

1. Position of the oiling Nozzle (d_r) for bearings with TA cage/ TXM cage upon request
2. The stated load and speed values are given for a spring preloaded single bearing with oil/air or oil mist lubrication. If specific applications differ, please consult correction factors and/or GMN USA engineers.